

SPECIAL PROVISIONS FOR BURIED UTILITY

1. No work provided for herein shall be performed until the Holder shall have given 48 hours notice to the Area Supervisor.
2. A copy of the permit or franchise must be on the job site, and protected from the elements, at all times during any of the construction authorized by said permit within the County's right-of-way.
3. Work shall be restricted to the hours between 8:00 a.m. and 4:30 p.m. or as directed by the Area Supervisor, and no work shall be allowed on the right-of-way Saturdays, Sundays, or Holidays.
4. In the event any mile post, right-of-way marker, monument, fence or guard rail is located within the limits of this project and will be disturbed during construction, these items will be carefully removed prior to construction and reset or replaced at the conclusion of construction to the satisfaction of the County. All signs and traffic control devices must be maintained in operation during construction.
5. If determined necessary by the Area Supervisor, any or all of the excavated materials shall be removed and replaced with suitable material as specified by the Area Supervisor.
6. Trenches shall be backfilled as soon as possible behind the laying of pipe or cable. No open trenches shall be left overnight.
7. All road surfaces, slopes, ditches, pipes, etc. disturbed and/or damaged by this operation shall be restored to their original condition and cross-section. All open trenches shall be marked by warning signs, barricades, and lights; and if necessary, flagmen shall be employed for the purpose of protecting the traveling public.
8. Where final location has been altered from design location, the permit holder shall furnish "as-built" plans to the County. Any field revisions will require prior approval of the County Area Supervisor. Permanent surface markers shall be placed to identify the location in the field.
9. The buried utility shall be placed as described with a minimum cover of 40 inches below ground surface.
10. In the construction and/or maintenance of this facility, the permit holder shall comply with the "Manual on Uniform Traffic Control Devices for Street and Highways."
11. In the event that construction and maintenance of the road facility within the proximity of the utility installation becomes necessary during the period which the utility will occupy a portion of the right-of-way, it is expressly understood that upon request from the County's representative, the utility company will promptly identify and locate by suitable field markings any and all of their underground facilities so that the County can be fully apprised at all times of its precise location.
12. The permittee agrees to relocate and/or remove its facilities, at no cost to the County, when requested to do so by Grays Harbor County Public Works Department.
13. No excavation or burial shall be within the roadside ditches.
14. No excavation or burial is allowed within two feet of roadway surface.
15. Upon completion, notify a Permit Coordinator at 360-249-5579.

16. Utility pedestals shall remain clear of vegetative material in order that they remain visible. A flex post shall mark the pedestals: yellow for gas lines, orange for communication lines, and red for PUD lines. The flex posts shall be placed alongside the above ground installations and have a minimum height of four (4) feet above the ground.